Gas Tankless Water Heater Connection Kits

Everything you need for easy installation

Now you can get everything you need for a gas tankless water heater installation in one comprehensive kit. Our all-in-one gas connector kits with factory-approved components keep your projects flowing.

Greater Productivity

- Easier, faster installation
- No field stripping or cutting

Fewer Leak Points

• Reduces the need for pipe nipples, 90s, and elbows

Simplified Maintenance

• Flush and purge points



Dormont.com

Complete Connection Kits – with Everything You Need





Single Union Service Valve Set 3/4" union for connection to water heater and 3/4" FPT for connection to water supply line



Select from a dozen options to get the best gas tankless water heater kit for your needs.

Kits Include

- Single Union Service Valve Set
- High BTU Flexible Gas Connector for Indoor/Outdoor Installations
- Full Port Gas Ball Valve

(See the full list of kit options on the back page.)

Service Valve Set

- Valve set replaces up to 18 fittings and 16 connections used in typical tankless water heater installations
- Full port, 1/4 turn ball valves with color-coded tee handles and union for fast identification
- Integrated 1/4 turn purge and drain valve allows for fast and easy testing and maintenance
- Includes 3L pressure relief valve rated to 370K BTU, ¾".
 MIP connection to service valve and ¾" FIP connection to drain pipe
- Staggered connection points for ease of installation and access
- No additional adapters required

41 Series High BTU Gas Connector

Heavy-duty, antimicrobial, hot-dipped gray PVC coating for unmatched protection from weather and abuse, Ideal for outdoor installations

40C Series High BTU Gas Connector

Premium yellow polymer coating features enhanced corrosion resistance, flame/smoke resistance and an antimicrobial additive that inhibits the growth of bacteria, mold, and mildew.

High BTU Stainless Steel Gas Connector

The Ideal Solution For Tankless Water Heaters

Increases Productivity

- Eliminates the need for pipe nipples, 90's and elbows
- Pre-fabricated gas connector means no field threading, cutting or assembly of CSST fittings and tubing

Quality Construction

- CSA design certified for indoor and outdoor applications
 - Durable 304 stainless steel
 - Exclusive No-Neck[®] Design increases flexibility
 - More corrugations per inch increase flexibility and extend service life
 - 100% Leak Tested
 - Use with Natural and LP (propane) gases
 - The yellow gas connector features a premium antimicrobial coating to inhibit bacteria growth, improve corrosion and UV

protection, and enhance flame and smoke resistance

- Premium antimicrobial coating for increased safety, durability, and longevity
 - Limited lifetime warranty for details visit

www.watts.com/resources/warranty-information

ULTRA

SAFETY SHIELD

()

Why Dormont

*Applies to premium yellow gas connector only

Dormont draws on decades of experience delivering high quality stainless steel to the commercial food service, residential, and OEM markets. To date, there are more than 180 million Dormont installations worldwide.

We manufacture connectors at our stateof-the-art facility in Export, PA, and offer the widest range of gas connectors, installation kits, and accessories for indoor and outdoor gas appliance needs.

Gas Tankless Water Heater Connection Kits

Kits come with Dual or Single Union Service Valve Set, High BTU Gas Connector, Full Port Gas Ball Valve, Thread Sealant and Leak Solution

Model Number	Description	Ordering #
SINGLE UNION LFTV75FKIT18NW	Single Union Service Valve set, 18" Ultra Flow Gray PVC Coated High BTU Gas Connector, Full Port Gas	0242443
LFTV75FKIT24NW	Single Union Service Valve set, 24" Ultra Flow Gray PVC Coated High BTU Gas Connector, Full Port Gas	0242444
SINGLE UNION LFTV75FKIT18NW-CV	Single Union Service Valve set, 18" SafetyShield Enhanced Yellow Coated High BTU Gas Connector, Full Port Gas Ball Valve	68004829
LFTV75FKIT24NW-CV	Single Union Service Valve set, 24" SafetyShield Ehanced Yellow Coated High BTU Gas Connector, Full Port Gas Ball Valve	68004682

Packaging Specifications: Kit Box dimensions: 18" W x 14-3/4" H x 4-1/2" D; Average weight: 9lbs. 2-pack Master Carton dimensions: 16" W x 18-1/2" H x 11" D; Average weight: 19.5lbs.

*The wetted surface of our Lead Free products contacted by consumable water contain less than one quarter of one percent (0.25%) of lead by weight.

BTU Chart for Ultra Flow High BTU Gas Connector

18-(318,500 BTU/hr NAT) (509,600 BTU/hr LP)

24-(290,900 BTU/hr NAT) (465,440 BTU/hr LP)

